



Technical specification





# Winston LFP260AH cell



## Winston LFP260AH cell

Specifications		
Model name	LFP260AHA	Alternative product marking TS-LFP260AHA, WB-LYP260AHA
Nominal voltage	3.3 V	Operating voltage under load is 3.0 V
Capacity	260 AH	+/- 5%
Operating voltage	max 3.8 V - min 2.8 V	
Deep discharge voltage	2.8 V	The cell is damaged if voltage drops below this level
Maximal charge voltage	3.8 V	The cell is damaged if voltage exceeds this level
Optimal discharge current	< 130 A	0.5 C
Maximal discharge current	< 780 A	3 C, continuous for max 15 minutes from full charge
Max peak discharge current	< 2600 A	10 C, maximal 5 seconds in 1 minute
Optimal charge current	< 130 A	0.5 C
Maximal charge current	< 780 A	< 3 C with battery temperature monitoring
Maximal continuous operating temperature	65 °C	The battery temperature should not increase this level during charge and discharge
Dimensions	283 X 362 X 55,5	Millimeters (tolerance +/- 2 mm)
Weight	8,7 kg	Kilograms (tolerance +/- 150g)
Optimal torque force	35 - 40 Nm	





 **PRODUCT WEBPAGE** 



GWL a.s.  
Průmyslová 11, 102 00 Prague 10  
Czech Republic, European Union