



You Power The Life  
[www.elerix.com](http://www.elerix.com)

Technical specification

# ELERIX EX-L50

## High Power LFP Cell

LiFePo4  
Lithium Iron Cell

**3.2V / 50Ah / 4C**

EX-L50



- ▶ High Power Cell - up to 4C - 200A Discharge
- ▶ Lithium Iron Phosphate - LiFePO4 Chemistry
- ▶ Long Cycle and Calendar Life (3000 cycles / 15 years)
- ▶ Wide Temperature Range, Including Sub-Zero Operation
- ▶ Superior quality and safety. No toxic chemicals

# ELERIX EX-L50

LiFePo4, Lithium Iron Cell  
3.2V / 50Ah / 4C



## ELECTRICAL CHARACTERISTICS

Items	Specification	Remarks		
Product code	EX-L50			
Nominal Voltage (V)	3.2			
Nominal Capacity (Ah)	50	Charge @0.5C, Discharge @0.5C		
Nominal Energy (Wh)	160			
Form Factor	130/150 size			
Terminal type	Screw M10 Bolt			
Terminal material	Copper (-) / Alu (+)			
Cell Dimension (mm)	Width	130		
	Height	149	Without terminals	
	Thick	36		
Cell Volume (dm <sup>3</sup> - L)	0.70			
Nominal Weight (kg)	1.37	Average value		
Energy Density	Gravity (Wh/kg)	117		
	Volume (Wh/L)	229		
Internal Resistance mOhm (Max)	1.3			
Voltage	Minimal (V)	2.5		
	Maximal (V)	3.65		
Current	Charge	Standard (A)	25	
		Max. Cont. (A)	50	
	Discharge	Standard (A)	50	
		Max. Cont. (A)	200	≤ 3 min, temp ≤ 50°C
		Peak (A)	250	≤ 30 sec, temp ≤ 50°C
Cycle Life at 80% DOD	3000	@0.3C/1C, @25°C, >80% SOH		
Operating Lifespan (Calendar Life)	15 years	Average material aging estimation		
Operating Temperature	Charge (°C)	-10 ~ +50 °C		
	Discharge (°C)	-20 ~ +60 °C		
	Storage (°C)	-20 ~ +45 °C		

## KEY SAFETY FEATURES

Items	Specification
Fire	No Self-ignition, No Explosion.
Overcharge	No Explosion. No Fire.
Short-circuit	No Explosion. No Fire.
Penetration	Smoke only. No Fire.
Crush	Smoke only. No Fire.
Overheating	Stable up to +130°C. No fire.
Non-toxic	No Cobalt, No Lead-Acid.
Recycling	+90% Recyclable.

Are you interested in more details?  
Visit our online presentation.

[PRODUCT WEBPAGE >](#)